

Product Specifications

Overhead Cranes



Product Summary

Light-duty overhead cranes designed for smooth, low-effort handling of glass components, reducing manual lifting risk and supporting efficient movement around factory work zones.

Specifications

- Designed for lift capacities of approximately 250 kg, 500 kg
- Commonly installed under existing gantry crane systems
- Bridge span typically up to 5 m, depending on load requirements
- Length configurable to suit the operating area
- Supports customer-supplied lifting equipment (e.g. vacuum suckers)
- Multiple bridge configurations are optional
- Freestanding or building-mounted support structure
- Painted finish for durability and workplace visibility
- Locally designed, engineered and installed

Options

- Lift capacity selection: 250 kg / 500 kg
- Multiple bridge rails for parallel workflows
- Custom spans and lengths based on the required load path
- Integration with vacuum lifters or specialised glass tooling
- Custom support structures for limited-space environments

Key Features

Smooth, Effortless Movement

Bridge and trolley follow the operator's motion to minimise strain, fatigue, and injury risk.

High-Quality Trolley System

German-engineered bridge and trolley components ensure precise, reliable lifting.

Configurable for Any Work Area

Span, reach and number of bridges tailored to factory layout and workflow.

Flexible Structural Support

Available as freestanding systems or mounted to an existing building structure.



Contact Us

500 A Wairakei Road, Harewood,
Christchurch
Email info@metalcraft.co.nz
Phone +64 3 360 3373

metalcraftglassracking.co.nz