

# Product Specifications

## Harp + Z Trolleys



## Product Summary

Factory trolleys for storing and moving single-glaze glass safely, with polymer-protected contact surfaces and secure slot-based retention.

## Specifications

### Harp Trolley

- 50-slot single-glaze harp trolley
- Approx. 1132 mm wide X 1000 mm deep X 1400 mm tall
- Plastic-coated 8 mm steel retention bars
- Slots approximately 8.2 mm wide for single glazing
- Kitset construction for ease of shipping
- Handles fitted for easy factory movement
- Rear lockdown feet for safe loading
- Non-marking polymer surfaces protect glass ends
- Hot dip galvanised or painted finish and welded construction.

### Z-Trolley

- 50-slot single-glaze harp configuration with top "Z" supports
- Approx. 1132 mm wide X 1000 mm deep X 1800 mm tall
- 8 mm plastic-coated bars with single horizontal Z support row
- Slots approximately 8.2 mm wide (12 mm optional) standard. Options of 8.2 mm and 12.5 mm and custom
- Non-marking polymer contact surfaces on key supports
- Four turning castors rated to approximately 460 kg each
- Kitset construction for compact shipping
- Painted or hot-dip galvanised finish options
- Welded or kitset construction for reduced shipping costs

## Options

### Harp Trolley

- Colour-coded harp separators
- Galvanised or painted finish choices
- Adaptable retention system for DGU handling

### Z-Trolley

- Custom slot width for thicker glass units
- Single or dual top Z support rows
- Adaptable DGU retention solutions

## Key Features

### Single-Glaze Slot Retention

Glass sits in slotted bases to keep sheets separated and stable during movement.

### Non-Marking Polymer Protection

Polymer coatings on contact bars and frames prevent scratching and edge damage.

### High-Capacity Castors

Four heavy-duty turning castors ensure smooth manoeuvring and long working life.

### Factory-Safe Lockdown Feet

Rear stabilising feet secure the trolley during loading and unloading.



## Contact Us

500 A Wairakei Road, Harewood,  
Christchurch

Email [info@metalcraft.co.nz](mailto:info@metalcraft.co.nz)

Phone +64 3 360 3373

[metalcraftglassracking.co.nz](http://metalcraftglassracking.co.nz)