

Product Specifications

Tooth Trolleys



Product Summary

Factory trolley designed for safe storage and access to double-glazed units, with protective “tooth” retention system and compact footprint for efficient space use.

Specifications

- Standard model: 30-slot DGU tooth trolley
- Approx. 1250 mm wide X 700 mm deep X 1200 mm tall
- 18-35 mm slot width to suit DGUs
- Two turning castors with brakes rated to ~460 kg each
- Two fixed castors rated to ~460 kg each
- Kitset or fully welded construction for long-term durability
- Plastic-rubber compound protects and secures glass
- Polymer leading edge supports safe loading and unloading
- Aluminium or steel construction.

Options

- Custom slot sizes to suit specific glazing products
- Safety colour coding for production areas
- Branding and identification signage
- Multiple footprint and height configurations
- Adaptation for transport loading where required

Key Features

Fast, Safe Individual Access

Tooth-style retention enables quick handling of individual DGUs while reducing the risk of damage.

Designed for Double Glazing

18-35 mm slot sizing accommodates variable DGU thickness and keeps sheets securely separated.

Heavy-Duty Castor System

A combination of locking and fixed castors supports smooth manoeuvring and controlled positioning.

Compact Space Usage

Efficient footprint maximises storage per m² while keeping units upright and contained.



Contact Us

500 A Wairakei Road, Harewood,
Christchurch
Email info@metalcraft.co.nz
Phone +64 3 360 3373

metalcraftglassracking.co.nz