

Product Specifications

Site Trestles



Product Summary

Folding site trestles with height adjustability and non-marking tops, designed for stable window installation work on uneven ground.

Specifications

- Construction: Aluminium frame with galvanised hinge brackets
- Top bar: T6 aluminium with inlaid non-marking polymer
- Standard length: 1200 mm (custom sizes available)
- Height adjustment: 660-975 mm in increments
- Storage: Folding design for compact transport
- Application: On-site installation work

Options

- Custom lengths to suit specific jobs
- Polymer surface variations for product type
- Branding or colour finishes available
- Additional stability accessories on request

Key Features

Lightweight & Strong

Aluminium construction with galvanised steel hinge brackets delivers durability without excess weight.

Fast On-Site Setup

Pinned-leg design folds out quickly, minimising downtime and simplifying transport between jobs.

Non-Marking Work Surface

T6 aluminium top extrusion with inlaid polymer protects frames and allows swarf to shed away from finished surfaces.

Adjustable for Uneven Ground

Height adjustment from 660-975 mm ensures a safe, level work surface on variable site conditions.



Contact Us

500 A Wairakei Road, Harewood,
Christchurch
Email info@metalcraft.co.nz
Phone +64 3 360 3373

metalcraftglassracking.co.nz