

Product Specifications

Hard-sided Trailers



Product Summary

Heavy-duty hard-sided site trailer designed for transporting machinery, windows and equipment with a low centre of gravity, secure enclosure and optional internal fitouts.

Specifications

- Approx. 4000 mm length plus drawbar (custom options available)
- Fibreglass front, roof and rear panels
- Low deck height with body fitted inside wheel track
- Internal open cavity with tailored fitout options
- Electric brakes for rated loads (up to 3500 kg GVM)
- Aerodynamic front section with additional storage space
- Welded chassis construction
- Designed and fabricated in New Zealand

Options

- Pull-out loading ramps
- Shelving and equipment storage compartments
- Load securing points and tie-down locations
- Body configuration over wheels if required
- Branding, signage and paint finish options
- Custom lengths and height clearances

Key Features

Low, Stable Towing Profile

Main body positioned inside the wheels for improved balance and safer road handling.

Durable Hard-Sided Protection

Fibreglass front, roof and rear panels protect high-value equipment from weather and road debris.

Custom Internal Fitouts

Open cavity configured with shelving, tie-downs or compartments to suit specific load types.

High Load Rating

Designed to a maximum of 3500 kg GVM with electric brakes for reliable transport of heavy equipment.



Contact Us

500 A Wairakei Road, Harewood,
Christchurch
Email info@metalcraft.co.nz
Phone +64 3 360 3373

metalcraftglassracking.co.nz